



▶ Zerust® Outdoor Preservation Shrink

Use Zerust®/Excor® ICT®510-OPS VCI Shrink Film for long-term outdoor storage and mothballing of parts and equipment. Zerust outdoor preservation film provides superior corrosion and UVI protection for up to 3 years even in extreme conditions.

Zerust/Excor Outdoor Preservation VCI Shrink Film provides advanced protection to metals with Zerust Vapor Corrosion Inhibitor (VCI) technology. It is a premium 8-mil, high-strength shrink film with UV stabilizers for 3-year outdoor protection. The film shrinks and conforms to objects when heated to repel moisture and contaminants. Zerust VCI saturates the interior of the packaging to protect hard-to-reach spaces and voids from corrosion.

This specially designed VCI shrink film is ideal for lay-up and mothballing of equipment, vehicles and outdoor storage of components. Multiple sheets can be shrunk together for any size application such as structures and machinery. Zerust Outdoor Preservation Film protects valuable metal assets and makes them ready to use whenever and wherever they are needed.

▶ Benefits

- High strength and performance
- 3-year outdoor protection
- Proven corrosion and UV protection
- Excellent shrink properties
- Superior handling and drape
- Safe for electronics

Application Type

- Storage
- Shipping
- Works with Zerust VCI diffusers

Application Example

Valuable assets are protected from corrosion when stored outdoors. Zerust film enables items to be stored near the project site and be operationally ready.



Specifications



Product Information Zerust®/Excor® ICT®510-OPS Film is a heat responsive durable film that shrinks and forms a durable package.

Appearance Typical colors are opaque gray and clear. Additional colors and printing available upon request.

Protected Metal Types Ferrous metal protection. Multimetal and non-ferrous protection are available upon request.

Protection Duration Outdoor UV protection for up to 3-years. Under shelter, VCI protects clean metals for years when used correctly and utilized within three years from receipt.

Storage Store in original packaging away from direct sunlight in conditions below 85°F (30°C) and 50% RH until ready for use.

Property	Direction (Machine or Transverse)	Zerust High-Strength Shrink Film*	Competitor Shrink Film	ASTM Test Method
Film Thickness	-	8.0 mil (203 µm)	10.5 mil (267 µm)	D-6988
Dart Impact Resistance	-	900 g	715 g	D-1709
Tear Strength	MD	15250 mN	18850 mN	D-1938
	TD	17280 mN	21800 mN	
Tensile Strength at Yield	MD	1552 psi (10.7 MPa)	1523 psi (10.0 MPa)	D-882
	TD	1537 psi (10.6 MPa)	1523 psi (10.0 MPa)	
Tensile Strength at Break	MD	3466 psi (23.9 MPa)	2756 psi (19.0 MPa)	D-882
	TD	3263 psi (22.5 MPa)	2900 psi (20.0 MPa)	
Elongation at Break	MD	930%	816%	D-882
	TD	895%	873%	
Breaking Factor	MD	26 lb/in	29 lb/in	D-882
	TD	24 lb/in	30 lb/in	
Water Vapor Transmission Rate 100°F (38°C), 100% RH	-	0.108 g/(100 in ² /day) 1.64 g/(m ² /day)	0.0924 g/(100 in ² /day) 1.43 g/(m ² /day)	F-1249
Vapor Inhibiting Ability (VIA)	-	Pass	-	NACE TM0208-2013

* Typical values, not meant to be a specification.

Availability

Custom options and printing available upon request. Minimum order quantities apply.

Stock Offerings:

PN 100-F-00070
8 mil 20' x 100' Opaque Gray
PN 100-F-00077
8 mil 40" x 425' Clear

Accessories:

PN 250-X-00002 (12 rolls/case)
6 mil 4" x 180' gray preservation tape
PN 250-X-00003 (8 rolls/case)
6 mil 6" x 180' gray preservation tape

Recyclable

Dispose of in accordance with local, national and international regulations. Check on options for recycling and incineration.

Safety

- Safe for people. This product does not pose a health hazard to users due to its classification as an article according to EU REACH, UN GHS, US OSHA HazCom and CA WHIMS regulations.
- Zerust VCI chemistry is safe for sensitive electronics. No galvanic effects, residues or changes in the properties of metals. The protective molecules dissipate upon opening of package.

PARS SANAT KEYMAND

Address: 3rd Floor, No. 21, Fatemi St., Valiasr Ave., Tehran-Iran
Tel.: (+98 21) 8896 8639 Fax: (+98 21) 8896 6464
E-mail: info@parssk.com WWW.PARSSK.COM