

Zerust® Axxanol™ Spray-G

For superior corrosion protection in a sprayable grease, use Zerust®/Excor® Axxanol Spray-G. It protects in extreme conditions, such as during outdoor storage and overseas shipping.

Axxanol Spray-G provides the protection of a grease in the convenience of a sprayable form. It outperforms many other rust preventative coatings, while being easier to apply and remove, saving time and costs associated with corrosion control. The product has an oily grease consistency and provides advanced corrosion protection for parts and equipment for up to 1 year outdoors and 2 years indoors.

Axxanol Spray-G can be used as a light lubricant while it provides exceptional corrosion protection. The product is resistant to water and is compatible with packaging and most rubber and plastic materials. Test on a small area before use.

Benefits

Sprayable multimetal rust preventative coating

Protects in extreme outdoor conditions

Safe for paint and plastic

Non-hazardous* disposal

Removable with an alkaline cleaner

Application Example

A large piece of machinery was coated with Axxanol Spray-G before shipment overseas. It was shipped on the deck and in extreme open-air conditions. The item arrived corrosion-free to the end customer.



Application Type

Storage
Shipping
During Operation
May be used with Zerust VCI packaging

*Non-Hazardous Disposal: Product in unopened original container prior to use is non-hazardous waste in the United States according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).



Technical Data

Product Information	Solvent-based corrosion inhibitor spray grease.	
Application	Apply via pressurized spray	
	Application temperature	50 to 90°F (10 to 32°C)
	Coverage	1 lb covers 211 ft ² (20 m ²)
	Layer Thickness	1 mil (25 µm)
	Removability	Alkaline cleaner
	VOC content	< 45%
	Flash Point	≥ 142° F (61° C)
	Viscosity at 104°F (40°C)	> 1123 mm ² per second
Protection Properties	Indoors	Up to 2 years
	Outdoor	Up to 1 year
	Salt Spray ASTM B-117	1500 Hrs @ 2 mil (50 µm)
	Packaging/Hermetically Sealed	Up to 5 years
	Metal types	Multimetal protection
Storage Guidelines	Temp	50 to 90°F (10 to 32°C)
	Duration	Up to 2 years

Availability

Zerust®/Excor® Axxanol™ Spray-G is sold in a ready-to-use aerosol can and in bulk pails and drums.

Part Number	Qty
350-M-00023AC	12 oz
350-M-00023PL	5 Gal
350-M-00023DR	55 Gal

Safety

- Product in unopened original container prior to use does not meet criteria for hazardous waste according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

PARS SANAT KEYMAND

Address: 3rd Floor, No. 21, Fatemi St., Valiasr Ave., Tehran-Iran
 Tel.: (+98 21) 8896 8639 Fax: (+98 21) 8896 6464
 E-mail: info@parssk.com WWW.PARSSK.COM