

Zerust® Axxatec™ 8110C Additive

Zerust®/Excor® Axxatec™ 8110 is an easy-to-use corrosion inhibiting additive that contains proven Zerust ICT® (Integrated Corrosion Technologies). Axxatec 8110 is designed for use in closed systems, such as aqueous cooling and hydraulic systems and will protect for up to six months.

Zerust® Axxatec™ 8110 protects interior surfaces and parts comprised of iron, steel, aluminum, copper and brass within closed systems. Axxatec 8110 is water-based and easily diluted with coolant or water-based hydraulic fluids. Use Zerust Axxatec 8110 to prevent corrosion in closed systems for up to six months. It is a water-based concentrate that can be added to fluids such as hydraulics and coolants.

In addition, Axxatec 8110 will provide a few hours of corrosion protection when used as a coating or final rinse for parts that will be enclosed in Zerust/Excor VCI Packaging Film. Axxatec 8110 helps prevent flash rust in-between production processes, but is not recommended as a long-term or stand-alone external corrosion protection coating.

Application Example

Hydraulics of diesel generators can be protected by Axxatec 8110 during downtime and storage.



Benefits

- Proven corrosion protection
- Protects multiple metal types
- Water-based concentrate
- Non-hazardous*

Application Type

- Storage
- Work in progress

*Non-Hazardous Disposal: Product in unopened original container prior to use is non-hazardous waste in the United States according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).



Specifications

Product Information	Zerust®/Excor® Axxatec™ 8110 is a water-based additive.	
Properties	Appearance	Light yellow liquid
	Removability	Deionized water
	pH	Approx. 6.8 - 7.8
Protection Info	Closed system	Up to 6 months
	Indoor	< 4 hours
	Outdoor	Not applicable
	Packaging/hermetically sealed	Up to 5 years
	Metal types	Ferrous, aluminum, copper and brass
Storage	Temp	50 to 90°F (10 to 32°C)
	Duration	Up to 2 years
Disposal	Dispose of in accordance with local, national and international regulations.	
Dilution	1 part Axxatec 8110 to 10 parts coolant or hydraulic fluid.	

Availability

Zerust® Axxatec™ 8110C is sold as a concentrate.

Part Number	Quantity
350-M-00005PL	5 Gal pail
350-M-00005DR	55 Gal drum

Health and Safety

Non-Hazardous Disposal: Product in unopened original container prior to use is non-hazardous waste in the United States according to 40 CFR 261 (no components listed on F, K, P or U lists; not ignitable, not corrosive, not reactive and not toxic).

PARS SANAT KEYMAND

Address: 3rd Floor, No. 21, Fatemi St., Valiasr Ave., Tehran-Iran
 Tel.: (+98 21) 8896 8639 Fax: (+98 21) 8896 6464
 E-mail: info@parssk.com WWW.PARSSK.COM